

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1010 1200  
Standard must be consulted for specific requirements.

Quick Identifier - Common  
Name Used on Label and List  
**SUMMER MELON**  
303-6540

## SECTION 1

*MAJESTIC MOUNTAIN SAGE*  
*918 WEST 700 NORTH STE 104*  
*LOGAN UT 84321*

Emergency Phone:  
(435) 755-0863

*National Paint & Coatings Association/HMIS Ratings:*  
*Health - 1, Flammability - 2, Reactivity - 0, Protective Equipment - C*  
*Minimal - 0, Slight - 1, Moderate - 2, Serious - 3, See Section 8-C*

Date Prepared:  
08-06-2002

## SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY

Haz List	Hazardous Components Chemical & Common Names	OSHA PEL	ACGIH TLV	NFPA	% Optional	CAS No.
(A, D)	AMYL ACETATE	100 ppm	100 ppm	130		628-63-7
(M)	ETHYL BUTYRATE			30		105-54-4
(D)	DIETHYL PHTHALATE		5 mg/m <sup>3</sup>	10		84-66-2

**If flashpoint in Section  
4 exceeds 141°F then this mixture is not restricted per IATA regulation 4.1.3.3**

Contributors to low flashpoint: AMYL ACETATE, ETHYL BUTYRATE

## SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point: UNKNOWN      Specific Gravity @ 25°C: .9741      Vapor Pressure (mm Hg): UNKNOWN

Vapor Density (Air = 1): UNKNOWN

Refractive Index: 1.4797 @ 25°C

Solubility in Water: INSOLUBLE

Reactivity in water: NONE

Appearance/Color/Odor: CLEAR LIQUID WITH TYPICAL, CHARACTERISTIC ODOR

## SECTION 4 - FIRE & EXPLOSION DATA

Flash Point: 110°F

Method Used: TCC

Flammable Limits in Air by Volume  
LEL Lower: UNKNOWN  
UEL Upper: UNKNOWN

Auto Ignition Temperature: UNKNOWN

Extinguishing Media: FOAM CARBON DIOXIDE OR DRY CHEMICAL

Special Fire Fighting Procedures: CLOSED DRUMS EXPOSED TO FIRE SHOULD BE COOLED BY A  
WATER SPRAY TO AVOID PRESSURE BUILDUP

Unusual Fire and Explosion Hazards: NONE

## SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)

Stability:

Unstable  
Stable

Conditions to Avoid: NONE

Incompatibility (Materials to Avoid): STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: NONE KNOWN

Hazardous Polymerization:

May Occur  
Will Not Occur

Conditions to Avoid:  
CONTACT WITH STRONG OXIDIZING AGENTS

## SECTION 6 - HEALTH HAZARDS

1. Acute - NOT ESTABLISHED

2. Chronic - NOT ESTABLISHED

Signs and Symptoms of Exposure: REDDENING AND BURNING SENSATION ON SKIN. DIZZINESS ON INHALATION.

Medical Conditions Generally Aggravated by Exposure: UNKNOWN

Chemical listed as Carcinogen or Potential Carcinogen

National Toxicology Program  
Yes  
No

I.A.R.C. Monographs  
Yes  
No

OSHA  
Yes  
No

Emergency and First Aid Procedures See Below

ROUTES OF ENTRY

1. Inhalation: Remove victim from contaminated area. Call physical. If not breathing begin resuscitation procedures promptly.

2. Eyes: Flush Eyes with running water for at least 15 minutes. Call a physician.

3. Skin: Wash with soap and water. Call a physician if there is any evidence of irritation or burning. Wash clothes before reuse.

4. Ingestion: unknown

## SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be taken in handling and storage:

Keep away from heat and open flame. Use with Adequate ventilation. Avoid exposure to vapors. Direct contact causes irritation of the eyes and skin. Avoid contact with eyes, skin and clothing. Wash thoroughly.

Steps to be taken in case material is released or spilled:

Dike spill and pump into salvage containers.

Waste disposal methods (consult Federal, State, and Local regulations):

Incinerate by injection into an open furnace. Disposal must comply with Local, State, and Federal regulations.

## SECTION 8 - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Respiratory Protection (Specific Type):

Use a NOISH/MESA approved respirator in confined or poorly ventilated areas.

Ventilation:

Local Exhaust: Yes, Mechanical (General): Yes, Special: N/A, Other N/A

Protective Gloves: NEOPRENE OR BUNA N

Eye Protection: CHEMICAL GOGGLES

Other Protective Clothing & Equipment: NONE

Work/Hygienic Practices:

Always wash hands after working with this product

No warranty is expressed or implied.

Testing to determine suitability in end user's product is the sole responsibility of the end user.